

BRETFORD BASICS™

UL Listed Wide-Body TV Carts for 25" to 27" Televisions

BBUL44, BBUL44-C4 and BBUL44-M4

Bretford's open shelf wide-body TV cart, BBUL44, BBUL44-C4 and BBUL44-M4 are UL listed for safety and have the strength and stability to support heavy audio visual equipment. Large television monitors of up to 27" diagonal screens are easily supported. The wide-body design provides an oversized base shelf for greater stability especially during transport and includes a safety belt for the monitor.



FEATURES

- Pyramid design and steel construction provide support for large monitors
- Recommended for use with up to a 27" diagonal TV monitor
- Meets UL standards for institutional audio visual carts
- 4" "Quite-Glide" stem casters, 2 fixed and 2 swivel with locking brakes
- Includes an adjustable SB safety belt to secure the monitor to the top shelf
- Steel construction with black powder paint finish
- BBUL44-C4 comes with a 2-outlet, UL-listed electrical unit with a 20 foot power cord and built in cord winder, BBUL44-M4 includes a 3-outlet, UL-listed electrical unit with a 20 foot power cord and built in cord winder.

DIMENSIONS

Overall: 32" w x 27 1/2" d x 44" h
Top Shelf: 32" w x 22" d
Bottom Shelf: 32" w x 27 1/2" d
Top to Middle Shelf: 10 1/2"
Middle to Bottom Shelf: 23"

COLOR & FINISH

Black (-BK) powder paint

STANDARD EQUIPMENT

32" w x 22" d Shelf (2)
32" w x 27" d Shelf (1)
1" square Black caster inserts (4)
1" square plastic tube caps (4)
4" fixed casters (2)
4" swivel casters with brake (2)
Plastic bag with all necessary hardware for assembly
Hex Wrench
Instruction sheet: Warranty information
User Safety Instruction Sheet/Safety Label
2 outlet electrical unit with BBUL44-C4 only
3 outlet electrical unit with BBUL44-M4 only

WEIGHT AND FREIGHT CLASS

BBUL44: 59 lbs.
BBUL44-C4: 62 lbs.
BBUL44-M4: 62 lbs.
All ship UPS ready-to-assemble in one carton pack.
Freight class 70 UPS.

CARTON DIMENSIONS & UPC CODE

Carton Packaging: 28 1/2" w x 6" d x 44 1/2" h
BBUL44 0 96633 10725 4
BBUL44-C4 0 96633 10726 1
BBUL44-M4 0 96633 12380 3

SUGGESTED SPECIFICATIONS

BBUL44 Wide-Body TV cart has two (2) 18-gauge steel 32" w x 22" d shelves and one (1) 18-gauge 32" w x 27 1/2" d shelf (to be used as the bottom or base of the cart). Shelves are press formed with a 1/8" lip bordering the top surface on all four (4) sides. Cart legs fit flush to the shelves and interlock with welded mounting brackets for added strength. Each corner has 13-gauge steel mounting brackets with 1/4" square head bolts and hex nuts that tighten to hold leg securely to shelf. The two (2) 32" w x 22" d shelves have two (2) 3/16" diameter holes centered on both the right side and the left side to accept an optional electrical assembly, standard with the BBUL44-C4 and BBUL44-M4. Top two shelves have a grommet hole at rear for cord management. Table legs are 18-gauge 1" square tubular steel. Each leg is 39 1/2" in length and are tapered so the top part fastens to a 32" w x 22" d shelf and the bottom of the leg fastens to a 32" w x 27 1/2" d base shelf. The cart stands 44" h from the floor (including the 4" casters). Leg has hard plastic caster insert mounted in the bottom of the tube. Each leg has a hard plastic cap detail inserted into the bottom of the tube. Each model has a durable powder paint finish. Casters are mar resistant hard black rubber and measure 4" in diameter. Two casters assembly have ball bearing swivel capabilities and a locking brake. Two casters are fixed. Optional electrical assembly is completely enclosed with two (-C4) or three (-M4) outlets, 20 ft. 3-wire cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to pre-drilled holes in the top shelves. Optional electrical assembly is UL listed when attached. BBUL44, BBUL44-C4 and BBUL44-M4. Wide-Body TV cart ships knocked down (KD) in one carton pack and ships via United Parcel Service (UPS).



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM