

# BRETFORD BASICS™

## ADJUSTABLE CABINET CART

### CA2642

Imagine, one cart that adjusts to meet all of your needs! Adjusting to multiple heights is as simple as resetting four screws. Open, roomy shelves provide ample storage space. Lower cabinet stores additional equipment. Black powder paint finish. Tops come with a rubber mat. Cart rolls easily on 4" casters.



### FEATURES

- Features a 5-height capability, from 26-42"H in 4" increments.
- Easily adjusts by resetting four screws.
- Durable all-steel construction with black powder paint finish.
- Includes a roomy lockable storage cabinet with two keys.
- Rolls smoothly on 4" "Quiet Glide" casters, 2 lock.
- Die-pressed shelves.
- Ribbed rubber mat for a non-slip top shelf.
- Recommended for use with up to 20" diagonal monitors.
- Optional UL and C-UL listed 2-outlet electrical unit with a 20 foot extension cord and cord winder, standard on the CA2642E.
- Steel content contains 30% post-consumer recycled steel.
- Optional Big Wheel kit includes two 8" rigid wheels and two 5" swivel casters.

## DIMENSIONS

Overall: 24"W x 18"D x 26-42"H

Shelf: 24"W x 18"D

Cabinet Interior: 23-1/2"W x 17-1/2"D x 15-1/2"H

## COLOR & FINISH

Black (BK) powder paint

## STANDARD EQUIPMENT

24"W x 18"D Shelves (3)

1" round plastic caster insert (4)

4" diameter casters (4)

18" x 24" Rubber Mat (1)

Keys for cabinet lock (2)

2 outlet electrical unit (1) [CA2642E only]

## WEIGHT AND FREIGHT CLASS

55 lbs., Freight class 85 UPS

Ships ready to assemble in one (1) carton pack

## ACCESSORIES

E-Unit Electrical assembly with 2 grounded outlets, 20 ft. grounded extension cord. UL listed when mounted on table. Standard on CA2642E

ES-Unit Electrical assembly with 3 grounded outlets, 20 ft. grounded extension cord. UL listed when mounted on table.

044-0025 5" caster pak with 2 locking brakes (can substitute for 4")

044-0026 Big Wheel Kit

RM1824 Rubber mat for 18"W x 24"D shelf

SB Safety Belt 8 ft. in length to hold equipment

EPS Surge Protected Power Strip

## CARTON DIMENSIONS & UPC CODE



20-3/4"W x 23-1/2"D x 26-3/4"H

CA2642: 0 96633 10005 7

CA2642E: 0 96633 10575 5

## SUGGESTED SPECIFICATIONS

CA2642 Adjustable Cabinet Table has three (3) 20-gauge steel 18" x 24" shelves. Shelves are press formed with a 1/4" lip bordering the top surface on all four sides. The top shelf has a 20-gauge steel stiffener electrically welded underneath the surface front to back. A Black rubber mat 18" x 24" is placed on the top shelf. Shelf has two (2) 3/16" diameter holes centered on the right side, left side and rear to accept an optional electrical assembly. Table has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs 21-1/4" long welded to the shelf at each corner. Each leg has two (2) 1/4" diameter holes near the bottom of the

section and in the center of the leg that will accept a 1/4-20 machine screw. The holes are spaced 4" apart to permit height adjustments of 26", 30", 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by the machine screw. The bottom section of the adjustable table consists of a 20-gauge steel cabinet of interior dimensions 23"W x 15-1/2"H x 17"D. There are four (4) 14-gauge steel 19" legs welded to the cabinet at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg that will accept a 1/4-20 machine screw. Constructed using "prime" steel which has a 25% to 35% post-consumer recycled content. Holes are 4" apart to permit table height adjustments (as noted above). Cabinet has one (1) 20-gauge steel stiffener spot welded top to bottom. Model has a black powder paint finish. A hard plastic caster insert is mounted to each leg. Casters are mar-resistant Black hard rubber and 4" in diameter. Each caster assembly has ball bearing swivel capabilities and steel construction. Two (2) have locking brakes. Optional electrical assembly is completely enclosed with two (2) grounded outlets. Includes 20 ft. 3-wire cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. Optional electrical assembly is UL Listed when attached. CA2642 Adjustable Cabinet Table ships assembled in one (1) carton via United Parcel Service (UPS).



11000 SEYMOUR AVENUE  
FRANKLIN PARK, ILLINOIS 60131 USA  
TOLL FREE PHONE 800-521-9614  
PHONE 847-678-2545  
TOLL FREE FAX 800-343-1779  
FAX 847-678-0852  
WWW.BRETFORD.COM