

BRETFORD BASICS™ OVERHEAD PROJECTOR CART

OH29

Select the overhead projector cart to organize your next presentation. Adjustable projector well allows you to place the projector at the correct height. Constructed of steel and finished in black powder paint, this mobile cart can be easily used in a variety of rooms.



FEATURES

- 29" height is convenient for desk side use.
- Folding drop leaves on either side of projector platform measure 11"W x 20-1/4"D.
- Large projector platform measures 17"W x 19-3/4"D.
- Projector shelf has four different heights, adjusting from 19-27-3/4"H.
- Narrow design allows the cart to be easily maneuvered through aisles and hallways.
- Smooth rolling 4" casters, two lock.
- Durable all-steel construction contains 30% post-consumer recycled steel and is finished in an environmentally friendly putty beige or black powder paint.
- Lower storage shelf holds supplies and reference materials.

DIMENSIONS

Overall (drop leaves down): 22-1/2" w x 19-3/4" d x 29" h

One drop leaf up: 30-1/2" w x 19-3/4" d x 29" h

Both drop leaves up: 39" w x 19-3/4" d x 29" h

Drop leaf panel: 11" w x 20-1/4" d

Projector platform: 17" w x 19-3/4" d

Bottom shelf: 17" w x 19-3/4" d

COLOR & FINISH

Putty Beige (-PB) or Black (BK) powder paint

STANDARD EQUIPMENT

Leg assembly (2)

Projector shelf (1)

Drop leaf panels (2)

1" square, plastic caster insert (4)

4" mar-resistant black casters (4)

Lower storage shelf

WEIGHT AND FREIGHT CLASS

OH29 and OH29-BK: 38 lbs., Freight class 85 UPS

OH29E and OH29E-BK: 40 lbs., Freight class 85 UPS

Ships ready to assemble in one (1) carton pack

ACCESSORIES

E-Unit Electrical assembly with 2 grounded outlets, 20 ft. grounded extension cord. UL listed when mounted on table.

CARTON DIMENSIONS & UPC CODE

22-3/4" w x 36" d x 6-1/4" h

OH29: 0 96633 10001 9

OH29-BK: 0 96633 16214 7

OH29E: 0 96633 10447 5

OH29E-BK: 0 96633 12697 2

SUGGESTED SPECIFICATIONS

(Fill in quantity) OH29 and OH29-BK Overhead Projector Cart(s), designate model OH29E and OH29E-BK when optional E-Unit is desired.) Unit is finished in a putty beige or black powder paint coating that is environmentally safe and is constructed from 18 gauge steel. Features include an overhead projector shelf that can be adjusted from 19"-27-3/4" from the floor in order to accommodate different sizes of overhead projectors. The unit features a one piece, press-formed platform with a 4" wide facing front, 3/4" lip on left and right sides, and 4" back facing that includes two (2) slots for mounting the optional electrical unit. Platform facing sides includes a 3/4" flange into which mounting holes are punched. Four (4) 18 gauge, 1" steel tube legs each have three platform mounting holes located 6" from the top and 2-5/8" center distance between holes to permit the aforementioned platform settings and one drop leaf

mounting hole located 1-1/2" from the top of the leg. Platform is mounted to each of the four legs using two 1/2" truss screws. Unit also features two (2) drop leaves made from press-formed 18 gauge steel. Leaf edges are smooth with 1" side lips and front and back facings that form a triangle that graduates from 1" to 3". Unit can be operated with both leaves up, down or with just one leaf up. Drop leaf folding mechanism is two steel 1/4" x 17/16" rivets with rivet caps that attach to the front and back facings of each drop leaf panel and the left and right leg assemblies. Cart is constructed using "prime" steel which contains 25% to 35% post-consumer recycled materials. A non-adjustable 17" w x 19-3/4" d, 18 gauge steel lower shelf attaches to each of the four legs. A 1" square black plastic caster insert is mounted to each leg. Four (4) casters are mar-resistant, black hard rubber and are 4" in diameter. Each caster assembly has ball-bearing swivel capabilities and steel construction. Two (2) casters have locking brakes. Table ships ready to assemble via UPS and comes in one carton pack.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM